IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Application No.

09/465,396

Filed

December 17, 1999

Title

MICROPHONE ARRAY DIFFRACTING

STRUCTURE

Inventor

Michael R. Stinson et al

Examiner

Group Art Unit

2747

INFORMATION DISCLOSURE STATEMENT Under 37 C.F.R. 1.97

The Honourable Commissioner of Patents & Trademarks, WASHINGTON, D.C. 20231, U.S.A.

March 13, 2000

Sir:

Under the provisions of 37 C.F.R. 1.97, including particularly subsections (g) and (h) thereof, and 37 C.F.R. 1.98 including specifically subsection (d) thereof, Applicant calls to the attention of the Examiner the following documents, copies of which are enclosed:

AA	US	5 742 693	Elko	1998
AB	US	5 539 834	Bartlett et al	1996
AC	US	5 592 441	Kuhn	1997
AD	US	4 802 227	Elko et al	1989
AE	US	4 904 078	Gorike	1990

AN "Super directivity design for a sphere-buffed microphone array", J. Acoust. Soc. Am. Vol. 103, No. 5, 130, 2897, May 1998, K. Kawahara & K. Fukodome.

- AO "A steerable and variable first-order differential microphone array", Intl. Conf. On Acoustics, Speech and Signal Processing, 1997, G. Elko and A. Pong.
- AP "A Method of Interpolating the Diffractive Information of the Sphere-Baffled Microphone in the Sound Field of Sperical Wave" Dept. Of Acoustic Design, Japan, K. Fukodome

These references were brought to the attention of the applicant. The relevance of these references are as follows:

- U.S. Patent 5,742,693: Elko considers the improved directionality obtained by placing a first order microphone near a plane baffle, giving an effective second order system. Unfortunately, the system described is unwieldy. Elko notes that when choosing baffle dimensions, the largest possible baffle is most desirable. Also, to achieve a second order response, Elko notes that the baffle size should be in the order of at least one-half a wavelength of the desired signal. These requirements render Elko unsuitable for applications requiring physically small arrays.
- U.S. Patent 5,539,834: Bartlett et al, discloses achieving a second order effect from a first order microphone. Bartlett achieves a performance enhancement by using a reflected signal from a plane baffle. However, Bartlett does not achieve the desired directivity required in some applications. While Bartlett would be useful as a microphone in a cellular telephone handset, it cannot be readily adapted for applications such as handsfree telephony or teleconferencing in which high directionality is desirable.
- U.S. Patent 5,592,441: Kuhn uses forty-two transducers on the vertices of a regular geodesic two frequency icosahedron. While Kuhn may produce the desired directionality, it is clear that Kuhn is quite complex and impractical for the uses envisioned for the applicant's invention.

U.S. Patent 4,802,227: Elko et al, addresses the signal processing aspects of microphone arrays. Elko et al however, utilizes costly signal processing means to reduce noise. The signal processing capabilities required to keep adaptively calculating the required real-time analysis can be prohibitive.

U.S. Patent 4,904,078: Gorike, uses directional microphones in eyeglasses to assist persons with a hearing disability receiving aural signals. The directional microphones, however, do not allow for a changing directionality as to the source of the sound.

Kawahara and Fukudome: Kawahara and Fukudome suggests that a rigid sphere can be used to advantage in beamforming. However they do not have the features and advantages indicated in the applicant's invention.

Elko and Pong: Elko and Pong discuss a six-microphone configuration mounted on a sphere. They noted that the presence of the sphere acted to increase the effective separation of the microphones.

Fukudome: Fukudome provides more background information on baffled microphones.

It should be noted that these three academic publications only consider the case of a rigid intervening sphere.

Applicant respectfully requests that these references be entered into the record of this application. The Examiner is requested to initial the appropriate area on the enclosed copy of PTO Form 1449, thereby indicating consideration by the Examiner of each of these references.

As this submission is being filed before the issuing of an office action, it is believed no fee is payable.

Applicant respectfully submits that the present claims are patentable over the references identified herein, and requests timely and favourable examination of this application.

Respectfully submitted PASCAL & ASSQCIATES

Harold C. Baker Registration 19333

HCB:ay
Pascal & Associates
P.O. Box 11121, Station H
Nepean, Ontario
K2H 7T8

			<u> </u>					01	•			
FORM PTO-1449 U.S. DEPARTMENT OF COMMERCE (REV. 7-80) PATENT AND TRADEMARK OFFICE LIST OF REFERENCES CITED BY APPLICANT (Use several sheets if necessary)					ATTY. DOCKET	SERIAL NO. 09/465,396 Stinson et al						
					1,320,00							
					APPLICANT M							
					FILING DATE December 17	GROUP 2747						
			II.S. P	ATENT DOCUME		•						
EXAMINER		DOCUMENT		NAME		CLASS	sus	FIUNC	DATE			
INITIAL	 	NUMBER	DATE				SUB CLASS	IF PE	DATE RTINENT			
	AA	5 742 693	Apr.21/98	Elko								
	AB	5 539 834	Jul.23/96	Bartlett e	t al							
	AC	5 592 441	Jan. 7/97	Kuhn				,				
	AD	4 802 227	Jan.31/89	Elko et al								
	AE	4 904 078	Feb.27/90	Gorike	· ·							
	AF						·					
	AG				, <u>, , , , , , , , , , , , , , , , , , </u>		-					
	АH											
	l						_1 . <u>.</u>	<u>!</u>				
		T	FOREIGN PATENT DOCUMENTS sug						ATION			
		DOCUMENT NUMBER	DATE	COUN	TRY	CLASS	CLASS	YES NO				
	ΑI				,							
	AJ											
	AK											
	AL											
	AM											
		<u> </u>	OVER DESCRIPTION	SENCE (Inches in the control of the	T4. 0 . 0			<u> </u>				
			OTHER REPER	TENCES (Including Author	, Tide, Data, Pertinent Pages	, Etc.)						
	AN		"Super directivity design for a sphere-buffed microphone array" J. Acoust. Soc. Am., Vol. 103, No. 5, May 1998, Kawahara and Fukudome									
	AO	"A steerab	"A steerable and variable first-oder differential microphone array", Intl. Conf. On accoustics, Speech and Signal, Processing, 1997, Elko and Pong									
	AP	"A Method of Microphone	"A Method of Interpolating the Diffractive Information of the Spere-Baffled Microphone in the Sound Field of Sperical Wave" Dept. Of Acoustic Design, Japan, Fukudome									
	AQ				-				-			
EXAMIN	ER			DF	ATE CONSIDERED)	·					

*EXAMINER: Initial if reference considered, whether or not citation is in conformance